













ACCESSORIES | LAMP OPTIONS

LAMP	COMMENTS	WATTAGE	BEAM ANGLE	FOR USE WITH
 Xenolux MR-8	8000 Average Life Hour	20	Wide	CG
		20N	Narrow	CG
 Halogen MR-8	4000 Average Life Hour	20	Wide	CG
 Xenolux MR-11	8000 Average Life Hour	20	Wide	MP
		20N	Narrow	MP
 Halogen MR-11	4000 Average Life Hour	20	Wide	MP
 Xenolux MR-16	8000 Average Life Hour	10	Wide	LO, LR, MU, RS, TE
		20	Wide	LO, LR, MU, RS, TE
		20N	Narrow	LO, LR, MU, RS, TE
		35N	Narrow	LO, LR, MU, RS, TE
		50	Wide	LO, LR, MU, TE
		50VW	Very Wide	LO, LR, MU, TE
 Halogen MR-16	4000 Average Life Hour	20	Wide	LO, LR, MU, RS, TE
		20V	Very Narrow	LO, LR, MU, RS, TE
		35	Wide	LO, LR, MU, RS, TE
		35V	Very Narrow	LO, LR, MU, RS, TE
		50N	Narrow	LO, LR, MU, TE
		50V	Very Narrow	LO, LR, MU, TE
 Xenolux T3	8000 Average Life Hour	10	N/A	BD, CA, CB, CM, CP, CR, CV, DL, DM, DP, DR, DS, EA, GT, LM, MM, PF, PR, PV, QF, RL, SC, SP
		20	N/A	BD, CA, CB, CM, CR, CV, DL, DM, DP, DR, DS, EA, GT, PF, PR, PV, QF, RL, SC, SP
		35	N/A	CM, CR, DR, DS, GN, RL
 Halogen T3	2000 Average Life Hour	20	N/A	SI
 Halogen AR-11	2000 Average Life Hour	20	Wide	CL, ML, PM, TC, TS, VL
		35	Wide	CL, TC, TS
 Halogen AR-20	2000 Average Life Hour	50N	Narrow	TS
 Incandescent 93	900 Average Life Hour	12	N/A	AL, FG, LS, TD
 Incandescent 1141	1200 Average Life Hour	18	N/A	AL, FG, TD

Beam Angle Key (approximate values)
 Very Narrow- 10°
 Narrow- 25°
 Wide- 40°
 Very Wide- 60°